

Hydraulic Workover / Snubbing Unit - 460K



The reliable and flexible 460K HWO / Snubbing Unit has been designed for all well situations: live / dead, onshore / offshore.

The jointed work string is handled by means of 4 hydraulic cylinders. The use of hydraulic cylinders allows perfect control over work string movements and makes it easy to use all types of downhole tools.

Advantages & Characteristics:

- Unique 'slip bowl interlock system'
- Small footprint
- Flexible
- Mobile
- Excellent cost / quality ratio
- Multi-purpose application
- 'A' Frame or direct well rig up

Operational Activities:

- Handling all types of completions
- Dead well operations
- Packer setting / milling
- Well clean outs
- Fishing operations
- Underbalance installation of liners
- Remedial operations
- Installation of velocity strings
- Snubbing operations
- P&A operations

TECHNICAL DATA

460K HWO UNIT

Max. Pull Capacity **460,000lbs**

Max. Push Capacity **225 Kips**

Rotary Torque **22,000 ft/lbs**

Stroke **10ft**

Through Bore **14-5/8"**

Gin Pole **3.2 tonne**

Superior Energy Services (Australia) Pty Ltd
6-10 Hunt Place, Wurruk VIC 3850. PO BOX 1114, SALE VIC 3853
☎ +61 3 5143 2225 🌐 www.superiorenergy.com.au

WELL INTERVENTION | RENTAL EQUIPMENT | MACHINING | FABRICATION

